

1080P EX-SDI Electric Socket Case Hidden Camera with Pinhole Lens



1/2.9 in SONY CMOS (IMX-222 / IMX-322) • Extended Serial Digital Interface • 1 Lux at F1.2 / 0.1 Lux (B/W)
• DNR(Digital Noise Reduction) • Day & Night (ICR Option) • Easy Installation

SPECIFICATIONS

Resolution	1080P
Sensor	1/2.9 inch SONY CMOS (IMX-222 / IM x 322)

1080P EX-SDI Electric Socket Case Hidden Camera with Pinhole Lens

Total Pixels	2000(H) × 1241(V) = 2,482,000
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (HD-SDI) / (CVBS: 1.0Vp-p (75ohm) : Option)
Min.Illumination	1 Lux at F1.2 / 0.1 Lux (B/W)
White Balance	AUTO
Electronic shutter speed	AUTO
DNR	ON
Day & Night	AUTO (Day <--> Night TIME Change)
Temperature/Humidity	Operating (14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH) / Storage (-4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH)
Power	Only DC12V
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (400M))