

**Eymax® Anti-IR Reflection Dome 2522 | 1080p EX-SDI/HD-SDI Outdoor IP68
+ Vandal-resistant Dome Camera, Fixed Lens, DC 12V, Small Size**



FEATURES

- 1/2.8 inch SONY CMOS
- 0 Lux at IR On (IR LED 02 pcs)
- Upgraded Waterproof Housing (IP 68 rating)
- DNR (Digital Noise Reduction)

Eyemax® Anti-IR Reflection Dome 2522 | 1080p EX-SDI/HD-SDI Outdoor IP68 + Vandal-resistant Dome Camera, Fixed Lens, DC 12V, Small Size

- Day & Night (ICR)
- Easy Installation
- 3.6mm (F1.5)

SPECIFICATIONS

Resolution	1080P, 720P
Sensor	1/2.8 inch SONY CMOS
Total Pixels	1945(H) × 1109(V) = 2.16M
Effective Pixels	1945(H) × 1097(V) = 2.13M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (EX-SDI, HD-SDI)
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
SENS_UP	OFF / × 2 ~ × 32
DNR / ACE	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / FLIP / MOTION / DEFOG	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness / Smart IR / Brightness	ADJUSTABLE (Sharpness : 0 ~ 10 STEP / Smart IR, Brightness : 0 ~ 20 STEP)
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating (−10°C ~ +50°C / 30% ~ 80% RH) / Storage (−20°C ~ +60°C / 20% ~ 90% RH)
Power	DC 12V
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (500M))