

Eyemax E2342 | 1080P(2MP) Night Color Turret 4-IN-1 Camera, Fix Lens, 130ft White LED Range, Built-in Mic



Full-color starlight • 40 m LED distance • Max. 30 fps @1080P • CVI / CVBS / AHD / TVI switchable • Built-in Mic • 2.8 mm Fixed lens • IP67, 12V 30% DC

Mount Accessories

Wall Mount Bracket	CWB-E204W
Junction Box	CJB-E139

Experience 1080P full HD color video and the simplicity of reusing existing coaxial infrastructure with HDCVI. The full-color starlight HDCVI camera presents a high quality color image with rich details even in total darkness conditions. It offers various fixed lens models with a multi-language OSD and HD/SD switchable output. It adopts two powerful warm white LED illuminators, covering an effective range up to 40m(131.23ft). The LEDs switch on automatically in darkness to capture detail-packed full-color images 24/7, ensuring authentic identification of objects. It is an ideal choice for applications such as schools, retail centers and parking lots.

Eyemax E2342 | 1080P(2MP) Night Color Turret 4-IN-1 Camera, Fix Lens, 130ft White LED Range, Built-in Mic

Full-color Starlight

The camera adopts F1.6 large aperture lens and 1/2.8" high performance sensor. With higher amount of absorbed light and advanced image processing algorithm, the camera presents an impressive lowlight performance with an exceptional balance between noise reduction and the blur of moving object.

Warm Supplemental lights

With two warm supplemental LED lights, the camera is able to provide a colorful and vivid image even in total darkness. It also provides visible By default, the camera is set to smart light mode, in which the camera can automatically adjust the exposure time and light sensitivity simultaneously to avoid overexposing of the objects in the image center. Also, the sensitivity and intensity of the LED lights can be remotely controlled by OSD menu.

Broadcast-quality Audio

Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology.

Long Distance Transmission

HDCVI technology guarantees long-distance and real-time transmission without any loss. It supports up to 800 m for 1080P Full HD video via coaxial cable, and up to 300 m via UTP cable.

Eyemax E2342 | 1080P(2MP) Night Color Turret 4-IN-1 Camera, Fix Lens, 130ft White LED Range, Built-in Mic

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Multiple-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments.

FEATURES

- Full-color starlight
- 40 m LED distance
- Max. 30 fps @1080P
- CVI / CVBS / AHD / TVI switchable
- Built-in Mic
- 2.8 mm Fixed lens
- IP67, 12V±30% DC

SPECIFICATIONS

Camera	
Image Sensor	1/2.8 inch 2.16 Mega Pixels CMOS

Eyemax E2342 | 1080P(2MP) Night Color Turret 4-IN-1 Camera, Fix Lens, 130ft White LED Range, Built-in Mic

Effective Pixels	1920 (H) × 1080 (V), 2MP
Electronic Shutter Speed	PAL: 1/25s - 1/100,000s NTSC: 1/30s ~ 1/100,000s
Minimum Illumination	0.005Lux / F1.6, 30IRE, 0 Lux white Light on
Fill Light (White Light) Distance	Distance up to 40m (131.23ft)
Fill Light On/Off Control	Auto; Manual
Fill Light Number	2
Pan / Tilt / Rotation Range	Pan: 0°-360° Tilt: 0°-78° Rotation: 0°-360°
Lens	
Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8mm
Max. Aperture	F1.6
Angle of View	126.2° × 106.0° × 56.5°(D x H x V)
Iris Type	Fixed iris
Close Focus Distance	0.6m (1.97ft)
DORI Distance	Detect 38.6m (126.6ft) / Observe 15.4m (50.5ft) / Recognize 7.7m (25.3ft) / Identify 3.9m (12.8ft)
Video	
Video Frame Rate	CVI: PAL - 1080@25fps, 720@25fps, 720@50fps NTSC ~ 1080@30fps, 720@30fps, 720@60fps AHD: PAL: 1080@25fps,720@25fps NTSC: 1080@30fps,720@30fps TVI: PAL: 1080@25fps,720@25fps,720@50fps NTSC: 1080@30fps,720@30fps,720@60fps CVBS: PAL: 960 × 576H; NTSC: 960 × 480H
Resolution	1080P (1920 × 1080); 720P (1280 × 720); 960H (704 × 576 / 704 × 480)
BLC	BLC / HLC / WDR
WDR	DWDR

Eyemax E2342 | 1080P(2MP) Night Color Turret 4-IN-1 Camera, Fix Lens, 130ft White LED Range, Built-in Mic

White Balance	Auto; Manual
Gain Control	Auto; Manual
Noise Reduction	2D DNR
Smart Light	Yes
Electronic Defog	Yes
Digital Zoom	16X
Mirror	Off/On
Privacy Masking	Off/On (4 area, rectangle)
Certification	
Certifications	CE (EN55032, EN55024, EN50130 ~ 4, EN60950 ~ 1) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4 ~ 2014) UL (UL60950 ~ 1+CAN/CSA C22.2 No.60950 ~ 1)
Interface	
Audio Interface	Built-in mic
Port	
Video Port	Video output choices of CVI / TVI / AHD / CVBS by one BNC port
Power	
Power Supply	12V \pm 30% DC
Power Consumption	Max 5W (12V DC, white light on)
Environment	
Operating Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Storage Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Protection Grade	IP67
Structure	
Casing	Metal throughout the whole casing
Dimensions	Ø106.0mm × 93.6mm (Ø4.17" × 3.69")
Net Weight	0.46Kg (1.01lb)
Gross Weight	0.61Kg (1.34lb)