

Eyemax E5132 | 5MP 4-In-1 Outdoor IR Turret Camera, Fixed Lens, UL-Listed, IR Range up to 98ft (30m), IP67, DC 12V



Max 25 fps@5MP (16:9 video output) • CVI / CVBS / AHD / TVI switchable • 2.8 mm fixed lens • Max. IR length 30 m, Smart IR • IP67, DC12V

Mount Accessories

Wall Mount Bracket	CWB-E203W
Junction Box	CJB-E136

FEATURES

- Max 25 fps@5MP (16:9 video output)
- Quick-to-install eyeball saves installation time
- CVI / CVBS / AHD / TVI switchable
- 2.8 mm fixed lens
- Max. IR length 30 m, Smart IR
- IP67, DC12V

System Overview

Experience 5MP full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 5MP HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-per-formance makes the camera an ideal choice for SMB solutions.

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility. (* Audio input is available for some models of HDCVI cameras.)

Easy Installation

HDCVI Quick-to-install eyeball adopts quick-to-install pedestal, which can achieve easier installation than conventional eyeball. Quick-to-install camera reduces time and labor costs.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700 m for 5MP HD video via coaxial cable, and up to 300 m via UTP cable.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu. This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of $\sim 40^{\circ}\text{C}$ to $+60^{\circ}\text{C}$ (-40°F to $+140^{\circ}\text{F}$), the camera is designed for extreme temperature environments. Supporting $\pm 30\%$ input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

SPECIFICATIONS

Camera

Eyemax E5132 | 5MP 4-In-1 Outdoor IR Turret Camera, Fixed Lens, UL-Listed, IR Range up to 98ft (30m), IP67, DC 12V

Image Sensor	1/2.7 inch CMOS
Max. Resolution	2880 (H) × 1620 (V)
Pixel	5MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s-1/100000s NTSC: 1/30s-1/100000s
S/N Ratio	65 dB
Min. Illumination	0.01 Lux/F1.6, 30IRE, 0 Lux IR on
Illumination Distance	30 m (98.4 ft)
Illuminator On/Off Control	Auto; manual
Illuminator Number	1
Pan / Tilt / Rotation Range	Pan: 0°-360° Tilt: 0°-78° Rotation: 0°-360°
Lens	
Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8 mm
Max. Aperture	F1.6
Field of View	2.8 mm: 132° × 111° × 58° (diagonal × horizontal × vertical)
Iris Type	Fixed iris
Close Focus Distance	2.8 mm: 0.9 m (3.0 ft)
DORI Distance	Detect : 63.6m (208.7 ft) Observe : 25.4m (83.3 ft) Recognize : 12.7 m (41.7 ft) Identify : 6.4 m (21.0ft)
Video	
Frame Rate (CVI)	PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps
Frame Rate (AHD)	PAL: 4M@25 fps; NTSC: 4M@30 fps
Frame Rate (TVI)	PAL: 4M@25 fps; NTSC: 4M@30 fps

Eyemax E5132 | 5MP 4-In-1 Outdoor IR Turret Camera, Fixed Lens, UL-Listed, IR Range up to 98ft (30m), IP67, DC 12V

Frame Rate (CVBS)	PAL: 960H; NTSC: 960H
Resolution	5M (2880 × 1620); 4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)
Day/Night	Auto switch by ICR
BLC	BLC / HLC / DWDR
WDR	DWDR
White Balance	Auto; manual
Gain Control	Auto; manual
Noise Reduction	2D NR
Smart IR	Yes
Mirror	Off / On
Privacy Masking	Off / On (8 area, rectangle)
Certifications	
Certifications	CE (EN55032:2015, EN 61000 ~ 3-2:2014, EN 61000 ~ 3-3:2013, N55024:2010+A1:2015, EN 55035:2017, EN50130 ~ 4:2011+A1:2014, EN 62368 ~ 1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4 ~ 2014) UL (UL60950 ~ 1+CAN/CSA C22.2 No.60950 ~ 1)
Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Power	
Power Supply	12V ±30% DC
Power Consumption	Max 3.2W (12V DC, IR on)
Environment	
Operating Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Storage Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Protection Grade	IP67
Structure	
Casing	Metal dome+metal cover+plastic decorative ring
Camera Dimensions	Ø109.9 mm × 88.1 mm (Ø4.33" × 3.47")
Net Weight	0.33 kg (0.73 lb)

Eyemax E5132 | 5MP 4-In-1 Outdoor IR Turret Camera, Fixed Lens, UL-Listed, IR Range up to 98ft (30m), IP67, DC 12V

Gross Weight	0.44 kg (0.97 lb)
--------------	-------------------