

Eyemax P4122 | 4MP EX-SDI Outdoor Turret IR Camera, IP67, Fixed Lens, 50ft (15m) IR Range, DC 12V



SPECIFICATIONS

Resolution	1440P
Lens	Fixed lens 2.8mm / 4mm
Sensor	1/2.8 inch SONY CMOS (IMX-335)
Pixels	Total : 2704(H) × 2104(V) = 5.69M / Effective : 2616(H) × 1964(V) = 5.14M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Frame Rate	4MP@30fps
Video Output	SMPTE274M EX-SDI (CVBS)
Min.Illumination	0 Lux at IR On (IR LED 20)
White Balance	Auto / Auto Ext / Preset / Manual

Eyemax P4122 | 4MP EX-SDI Outdoor Turret IR Camera, IP67, Fixed Lens, 50ft (15m) IR Range, DC 12V

Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
Function	DNR / ACE / WDR / BLC / HLC / Sens_up / Privacy / Flip / Motion / Defog / RS-485 / Sharpness / Smart IR / Brightness
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
Language	ENG, CHN, CHN(S), JPN, KOR
IR Distance	15M
Temperature/Humidity	Operating (-10°C ~ +50°C / 30% ~ 80% RH) / Storage (-20°C ~ +60°C / 20% ~ 90% RH)
Power	DC 12V
Dimensions	Ø 4.09 × 3.54 " (104 × 90mm)
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (100M) / EX-SDI (500M))