

Magic G2622 | Full Time Night Color 1080P(2MP) Outdoor Bullet Camera, 4-IN-1, IP67, Metal Body, Fixed Lens, 65ft (20m) White LED Range, 120dB True WDR, UTC, DC 12V, Small Size



2 MP High Performance CMOS • Up to 1920 × 1080 Resolution • Full Time Color • Fixed Lens • 3D DNR, 120dB True WDR • Up to 65 ft (20 m) White Light Range • Multiprotocol Output: TVI/AHD/CVI/CVBS • Up-the-Coax (HV-C) • IP67 Protection

2 MP Outdoor Full Time Color Bullet Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

Magic G2622 | Full Time Night Color 1080P(2MP) Outdoor Bullet Camera, 4-IN-1, IP67, Metal Body, Fixed Lens, 65ft (20m) White LED Range, 120dB True WDR, UTC, DC 12V, Small Size

It is equipped with a white light that has a range of 65 feet (20 meters).

Fixed lens options are optimized for viewing angles that fit any situation. 120dB True WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

FEATURES

- 2 MP High Performance CMOS
- Up to 1920 × 1080 Resolution
- Full Time Color
- Fixed Lens
- 3D DNR, 120dB True WDR
- Up to 65 ft (20 m) White Light Range
- Multiprotocol Output: TVI/AHD/CVI/CVBS
- Up-the-Coax (HV-C)
- IP67 Protection

SPECIFICATIONS

| Camera | |
|-------------------|---|
| Image Sensor | 2 MP progressive scan CMOS |
| Resolution | 1920 (H) × 1080 (V) |
| Frame Rate | 1080p @ 30 fps |
| Min. illumination | Color: 0.0005 lux @ (f/1.0, AGC on), 0 lux with white light |
| Shutter Time | 1/30 s to 1/50,000 s |
| Slow Shutter | Max. 16 times |
| Lens | 2.8mm fixed lens |
| Lens Mount | M16 |
| Day/Night | Color |
| Day & Night | Color |
| Angle Adjustment | Pan: 0° to 360°; tilt: 0° to 180°; rotate: 0° to 360° |
| Synchronization | Internal synchronization |

Magic G2622 | Full Time Night Color 1080P(2MP) Outdoor Bullet Camera, 4-IN-1, IP67, Metal Body, Fixed Lens, 65ft (20m) White LED Range, 120dB True WDR, UTC, DC 12V, Small Size

| | |
|----------------------|--|
| WDR | 120dB |
| Menu | |
| AGC | Yes |
| White Balance | Auto/manual |
| BLC | Yes |
| Privacy Mask | 4 programmable privacy masks |
| Motion Detection | 4 programmable areas |
| WDR | Yes |
| Functions | Brightness, sharpness, 3D DNR, mirror, smart light |
| Interface | |
| Video Output | 1 HD analog output |
| Switch Button | TVI/AHD/CVI/CVBS |
| General | |
| Operating Conditions | -40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC ± 25% |
| Power Consumption | Maximum 3 W |
| Protection Level | IP67 |
| Material | Metal |
| White Light Range | Up to 65 ft (20 m) |
| Communication | Up-the-Coax, protocol: HV-C (TVI output) |
| Dimensions | 7.14" × 2.75" × 2.68" (181.4 mm × 70 mm × 68 mm) |
| Weight | Approximately 0.86 lbs (390 g) |