

**Magic G2622 | Full Time Night Color 1080P(2MP) Outdoor Bullet Camera, 4-IN-1, IP67, Metal Body, Fixed Lens, 65ft (20m) White LED Range, 120dB True WDR, UTC, DC 12V, Small Size**



2 MP High Performance CMOS • Up to 1920 × 1080 Resolution • Full Time Color • Fixed Lens • 3D DNR, 120dB True WDR • Up to 65 ft (20 m) White Light Range • Multiprotocol Output: TVI/AHD/CVI/CVBS • Up-the-Coax (HV-C) • IP67 Protection

2 MP Outdoor Full Time Color Bullet Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

# Magic G2622 | Full Time Night Color 1080P(2MP) Outdoor Bullet Camera, 4-IN-1, IP67, Metal Body, Fixed Lens, 65ft (20m) White LED Range, 120dB True WDR, UTC, DC 12V, Small Size

It is equipped with a white light that has a range of 65 feet (20 meters).

Fixed lens options are optimized for viewing angles that fit any situation. 120dB True WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

## FEATURES

- 2 MP High Performance CMOS
- Up to 1920 × 1080 Resolution
- Full Time Color
- Fixed Lens
- 3D DNR, 120dB True WDR
- Up to 65 ft (20 m) White Light Range
- Multiprotocol Output: TVI/AHD/CVI/CVBS
- Up-the-Coax (HV-C)
- IP67 Protection

## SPECIFICATIONS

Camera	
Image Sensor	2 MP progressive scan CMOS
Resolution	1920 (H) × 1080 (V)
Frame Rate	1080p @ 30 fps
Min. illumination	Color: 0.0005 lux @ (f/1.0, AGC on), 0 lux with white light
Shutter Time	1/30 s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8mm fixed lens
Lens Mount	M16
Day/Night	Color
Day & Night	Color
Angle Adjustment	Pan: 0° to 360°; tilt: 0° to 180°; rotate: 0° to 360°
Synchronization	Internal synchronization

# Magic G2622 | Full Time Night Color 1080P(2MP) Outdoor Bullet Camera, 4-IN-1, IP67, Metal Body, Fixed Lens, 65ft (20m) White LED Range, 120dB True WDR, UTC, DC 12V, Small Size

WDR	120dB
<b>Menu</b>	
AGC	Yes
White Balance	Auto/manual
BLC	Yes
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable areas
WDR	Yes
Functions	Brightness, sharpness, 3D DNR, mirror, smart light
<b>Interface</b>	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
<b>General</b>	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Maximum 3 W
Protection Level	IP67
Material	Metal
White Light Range	Up to 65 ft (20 m)
Communication	Up-the-Coax, protocol: HV-C (TVI output)
Dimensions	7.14" × 2.75" × 2.68" (181.4 mm × 70 mm × 68 mm)
Weight	Approximately 0.86 lbs (390 g)