

**Magic G8332 | 8MP (4K) 4-in-1 Outdoor IR Dome Camera, IP67, Metal Body, Fixed Lens, 100ft (30m) IR Range, UTC, DC 12V, Vandal-resistant**



8.29 MP, 3840 × 2160 resolution • 2.8 / 3.6 mm Fixed Focal Lens • Smart IR, up to 30 m IR distance • 4 in 1 video output (switchable TVI / AHD / CVI / CVBS) • IP67, IK10

## **FEATURES**

- 8.29 MP, 3840 × 2160 resolution
- 2.8 / 3.6 mm Fixed Focal Lens

# Magic G8332 | 8MP (4K) 4-in-1 Outdoor IR Dome Camera, IP67, Metal Body, Fixed Lens, 100ft (30m) IR Range, UTC, DC 12V, Vandal-resistant

- Smart IR, up to 30 m IR distance
- 4 in 1 video output (switchable TVI / AHD / CVI / CVBS)
- IP67, IK10

## SPECIFICATIONS

Camera	
Image Sensor	8.29 megapixel progressive scan CMOS
Signal System	PAL/NTSC
Resolution	3840 (H) × 2160 (V)
Frame Rate	TVI: 8MP@12.5fps, 8MP@15fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps AHD: 8MP@15fps CVI: 8MP@12.5fps, 8MP@15fps CVBS: PAL/NTSC
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Speed	PAL: 1/12.5s to 1/50,000s NTSC: 1/15s to 1/50,000s
Lens	2.8 / 3.6 mm Fixed Lens
Horizontal Field of View	102.9° (2.8 mm), 79° (3.6 mm)
Lens Mount	M12
Day/Night	IR cut filter
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 to 355°, Tilt: 0 to 75°, Rotation: 0 to 355°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day / Night Mode	Auto / Color / BW (black and white)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	Global / BLC / HLC / DWDR
Noise Reduction	2D DNR
Language	English

# Magic G8332 | 8MP (4K) 4-in-1 Outdoor IR Dome Camera, IP67, Metal Body, Fixed Lens, 100ft (30m) IR Range, UTC, DC 12V, Vandal-resistant

Functions	Brightness, Sharpness, Smart IR
<b>Interface</b>	
Video Output	Switchable TVI / AHD / CVI / CVBS
<b>General</b>	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25% *You are recommended to use one power adapter to supply the power for one camera.
Power Consumption	Max. 2.2 W
Protection Level	IP67, IK10
Material	Metal
IR Range	Up to 100ft (30m)
Communication	Up-the-Coax
Dimensions	Φ 111 mm × 82.4 mm (Φ 4.4" × 3.2")
Weight	Approx. 0.80 lb. (365 g)