

MB5332V | Up to 5MP 4-in-1(TVI / CVI / AHD / CVBS) IR Outdoor Dome Camera w/ 4 COB IR range up to 115ft(35m), Motorized Vari-focal Lens, IP67, Vandal-Resistant, DC 12V



1/2.5" 5Mega Pixel Sensor • TVI up to 5MP@20fps, default output TVI 4M@30fps (Switchable) • TVI/CVI/AHD/CVBS 4-IN-1 • Motoried 2.8~12mm 5Mega Pixel Lens • IR Cut Filter, 2DDNR • 4 white power COB LEDs, 115ft(35m) IR Distance • Support UTC function, toggle cable

SPECIFICATIONS

Image Sensor	1/2.5" 5 Mega Pixel Sensor
--------------	----------------------------

MB5332V | Up to 5MP 4-in-1(TVI / CVI / AHD / CVBS) IR Outdoor Dome Camera w/ 4 COB IR range up to 115ft(35m), Motorized Vari-focal Lens, IP67, Vandal-Resistant, DC 12V

Effective Pixels	5.0 Mega Pixels
Built-in Lens	2.8 ~ 12mm 5Mega Pixel Lens
Signal System	PAL/NTSC
Horizontal Resolution	NTSC: 2560 × 1440P (30F/S 4MP output/ 2560 × 1944 (20F/S 5MP output) PAL: 2560 × 1440P (25F/S 4MP output) / 2560 × 1944 (20F/S 5MP output)
Sync. System	Internal Sync.
Video Output	TVI & CVI & AHD & CVBS Output
S/N Ratio	More than 50dB (AGC OFF)
DNR	2D
OSD Menu	Support
UTC	Support by UTC
White Balance	Auto Tracking White Balance
Shutter Speed	1/25 ~ 50,000Sec.
Weather-proof	IP67
Protection Level	IP67
Working Temperature	-10°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Power Requirement	DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on)
Weight	1.76 lbs (0.80kg)