

TD Series | 4CH Penta-brid DVR System, H.265, 5MP TVI / AHD / CVI / IP Camera + Analog



FEATURES

- 4 CH TVI / AHD/CVI 5MP / 4MP / 1080P / 720P / WD1 video input
- 4 CH DVRs default support 2 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP video input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timed / motion /AI recording
- Playback : 4 CH simultaneously playback
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration

TD Series | 4CH Penta-brid DVR System, H.265, 5MP TVI / AHD / CVI / IP Camera + Analog

- Support remote network transmission and remote surveillance with mobile device Multi-user online simultaneously
- Authorization management, log review and device status review
- 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

SPECIFICATIONS

Video	
Analog Video Input	BNC × 4 BNC interface (1.0Vp-p; 75Ω) TVI/AHD/CVI : 5MP/4MP/1080P/720P/WD1 (live)
IP Video Input	2CH Up to 5MP@30fps
Total Input	6CH
Output	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 BNC × 1 : CVBS (used as the main or spot output)
Compression	H.264 / H.265
Multi-screen Display	1 / 4 / 6 / 9
Audio	
Input	RCA × 4
Output	RCA × 1 (linear, 600Ω)
Two-way audio	Take up channel one audio input
Compression	G.711(U/A)
Record	
Resolution	5MP Lite / 4MP Lite / 1080P / 1080P Lite / 720P / WD1 / D1
Frame Rate (Analog Channel)	5MP Lite@10fps (PAL / NTSC) 4MP Lite / 1080P@12fps(PAL) / 15fps (NTSC) 1080P Lite / 720P / WD1 / D1@25fps (PAL) / 30fps (NTSC)
Frame Rate (IP Channel)	25fps (PAL) / 30fps (NTSC)
Bit Rate	32Kbps ~ 4Mbps

TD Series | 4CH Penta-brid DVR System, H.265, 5MP TVI / AHD / CVI / IP Camera + Analog

Mode	Manual, timer, motion, smart event
Playback	
Playback	4CH
Search	Time slice / time / event / tag search
Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
Function	Play, Pause, FF, FB, Digital Zoom, etc.
Alarm	
Mode	Manual, Motion, Exception, Smart event
Input	4CH
Output	1CH
Network	
Interface	RJ45 100Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP
Incoming Bandwidth	16Mbps
Outgoing Bandwidth	40Mbps
Client Connection	Max. 5 users access
Mobile Device	
OS	iOS, Andriod
Storage	
HDD	SATA × 1, up to 10TB
Backup	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes
Port	
RS 485	Yes (half-duplex), connect to PTZ or keyboard
USB	USB 2.0 × 2
Others	
Power Supply	DC12V / 2A
Consumption	≤ 10W (without HDD)

TD Series | 4CH Penta-brid DVR System, H.265, 5MP TVI / AHD / CVI / IP Camera + Analog

Dimensions	11.81(W) × 9.80(D) × 1.77(H) inches 300(W) × 249(D) × 45(H)mm
Working Environment	-10 ~ 50°C, 10% ~ 90% (humidity)
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE, REACH